

# CABT1/...

## 6 wire cable

**CABT1/50****CABT1/200**

### Special features

- 6 wire cable
- Length: 50 m or 200 m
- High capacitive symmetry
- HBM colour code
- 6x0.14 mm<sup>2</sup>
- TPE coating
- Flame retardant according to IEC 60332-2-2

### Technical Data

Type		1-CABT1/50 <sup>1)</sup>	1-CABT1/200 <sup>1)</sup>
Length	m	50	200
Cable coating colour	RAL	2002 (blood orange)	
Coating material	-	TPE	
Wire insulation	-	TPE	
Number of wires	-	6	
Wire cross section	mm <sup>2</sup>	0.14	
Wire resistance	mΩ/m	≤130	
Wire inductivity	μH/m	1,2 μH/m	
Capacity (core/core and core/shield)	pF/m	≤82	
Shield	-	1	
Outer diameter	mm	5.4 <sup>-0.3</sup>	
Temperature range	°C [°F]	-30 ... +120	
Wire colours (HBM colour code)	-	grey, black, white, blue, green, red	
Weight, approx.	kg	3	10.4

<sup>1)</sup> Ordering number

Subject to modifications.  
All product descriptions are for general information only.  
They are not to be understood as a guarantee of quality or  
durability.

**Hottinger Baldwin Messtechnik GmbH**

Im Tiefen See 45 · 64293 Darmstadt · Germany  
Tel. +49 6151 803-0 · Fax: +49 6151 803-9100  
Email: [info@hbm.com](mailto:info@hbm.com) · [www.hbm.com](http://www.hbm.com)

measure and predict with confidence

