

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



**BCY01**

Revision date: 16.03.2021

Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

BCY01

UFI: RJNT-SUVA-84MS-VRDH

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Activator

### 1.3. Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kjaer  
Street: Im Tiefen See 45  
Place: D-64293 Darmstadt  
Telephone: +49 (0)6151 803-0  
Internet: www.hbm.com  
Responsible Department: support@hbm.com

**1.4. Emergency telephone number:** +49-30-18412-0

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:  
Flammable liquid: Flam. Liq. 2  
Aspiration hazard: Asp. Tox. 1  
Germ cell mutagenicity: Muta. 1B  
Carcinogenicity: Carc. 1B  
Hazardous to the aquatic environment: Aquatic Chronic 2  
Hazard Statements:  
Highly flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
May cause genetic defects.  
May cause cancer.  
Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha cyclohexane  
n-hexane

**Signal word:** Danger

##### Pictograms:



##### Hazard statements

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H340 May cause genetic defects.  
H350 May cause cancer.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



BCY01

Revision date: 16.03.2021

Page 2 of 11

H411 Toxic to aquatic life with long lasting effects.

## Precautionary statements

P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

## Special labelling of certain mixtures

Restricted to professional users.

## Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



## Hazard statements

H304-H340-H350

## Precautionary statements

P201-P280

## 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			50 - 100 %
	265-151-9	649-328-00-1		
	Carc. 1B, Muta. 1B, Asp. Tox. 1; H350 H340 H304			
110-82-7	cyclohexane			5 - < 10 %
	203-806-2	601-017-00-1		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			
99-97-8	N,N-dimethyl-p-toluidine			0,1 - < 1 %
	202-805-4	612-056-00-9		
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 3; H331 H311 H301 H373 H412			
110-54-3	n-hexane			0,1 - < 1 %
	203-777-6	601-037-00-0		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			

Full text of H and EUH statements: see section 16.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



BCY01

Revision date: 16.03.2021

Page 3 of 11

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
99-97-8	202-805-4	N,N-dimethyl-p-toluidine	0,1 -< 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg	
110-54-3	203-777-6	n-hexane	0,1 -< 1 %
		STOT RE 2; H373: >= 5 - 100	

### Further Information

No information available.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

First aider: Pay attention to self-protection!

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.

#### After contact with skin

IF ON SKIN: Wash with plenty of soap and water.

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin reactions, consult a physician.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). IF

SWALLOWED: Immediately call a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), alcohol resistant foam, Extinguishing powder

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



BCY01

Revision date: 16.03.2021

Page 4 of 11

## 6.1. Personal precautions, protective equipment and emergency procedures

### General measures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

## 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

## 6.3. Methods and material for containment and cleaning up

### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Wash hands before breaks and after work.

Separate storage of work clothes.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

#### Further information on handling

No information available.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

#### Further information on storage conditions

No information available.

### 7.3. Specific end use(s)

Activator

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



BCY01

Revision date: 16.03.2021

Page 5 of 11

## Additional advice on limit values

No information available.

## 8.2. Exposure controls



### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

In use, may form flammable/explosive vapour-air mixture.

Use explosion-proof electrical equipment.

Use non-sparking tools.

### Protective and hygiene measures

When using do not eat or drink.

Do not breathe gas/fumes/vapour/spray.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

Wear suitable protective clothing, gloves and eye/face protection.

Draw up and observe skin protection programme.

### Eye/face protection

Wear eye/face protection.

### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Thickness of the glove material:  $\geq 0,7\text{mm}$

Suitable gloves type NBR (Nitrile rubber)

Breakthrough time:  $>480\text{ min}$

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### Skin protection

Used working clothes should not be worn outside the work area.

Separate storage of work clothes.

Wear anti-static footwear and clothing

### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device (full mask or mouthpiece) with filter: a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

### Environmental exposure controls

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Colour:

colourless

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



BCY01

Revision date: 16.03.2021

Page 6 of 11

Odour:	Solvent	
		<b>Test method</b>
pH-Value:		not determined
<b>Changes in the physical state</b>		
Melting point:		not determined
Boiling point or initial boiling point and boiling range:		93-97 °C
Sublimation point:		not determined
Softening point:		not determined
Pour point:		not determined
not determined:		
Flash point:		-4 °C
Sustaining combustion:		No data available
<b>Flammability</b>		
Solid/liquid:		not applicable
Gas:		not applicable
<b>Explosive properties</b>		
There are no data available on the mixture itself.		
Lower explosion limits:		0,84 vol. %
Upper explosion limits:		6,7 vol. %
Auto-ignition temperature:		205 °C
<b>Self-ignition temperature</b>		
Solid:		not applicable
Gas:		not applicable
Decomposition temperature:		not determined
<b>Oxidizing properties</b>		
There are no data available on the mixture itself.		
Vapour pressure:		47 hPa
(at 20 °C)		
Vapour pressure:		189 hPa
(at 50 °C)		
Density (at 20 °C):		0,7 g/cm <sup>3</sup>
Bulk density:		not determined
Water solubility:		not determined OECD 116
<b>Solubility in other solvents</b>		
not determined		
Partition coefficient n-octanol/water:		not determined
Viscosity / dynamic:		not determined
Viscosity / kinematic:		not determined
Flow time:		not determined
Relative vapour density:		not determined
Evaporation rate:		not determined
Solvent separation test:		not determined
Solvent content:		15,00 %

## 9.2. Other information

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



BCY01

Revision date: 16.03.2021

Page 7 of 11

Solid content:

not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

### Further information

No information available.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
99-97-8	N,N-dimethyl-p-toluidine				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation aerosol	ATE 0,5 mg/l			

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

May cause genetic defects. (Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha)

May cause cancer. (Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha)

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



BCY01

Revision date: 16.03.2021

Page 8 of 11

## Specific effects in experiment on an animal

No information available.

## Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

## Practical experience

No information available.

## 11.2. Information on other hazards

### Other information

No information available.

### Further information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Very toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
110-54-3	n-hexane					
	Acute fish toxicity	LC50	2,5 mg/l	96 h	Pimephales promelas	Geiger et al. 1990

### 12.2. Persistence and degradability

other non-biodegradable wastes

### 12.3. Bioaccumulative potential

No information available.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
99-97-8	N,N-dimethyl-p-toluidine	2,81
110-54-3	n-hexane	3,9

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

### 12.7. Other adverse effects

No information available.

### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.  
Wassergefährdungsklasse 2 - wassergefährdend

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Dispose of waste according to applicable legislation.

#### Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006



BCY01

Revision date: 16.03.2021

Page 9 of 11

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN 1206  
**14.2. UN proper shipping name:** HEPTANES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Limited quantity: 1 L  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

### Inland waterways transport (ADN)

**14.1. UN number:** UN 1206  
**14.2. UN proper shipping name:** HEPTANES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Limited quantity: 1 L  
Excepted quantity: E2

### Marine transport (IMDG)

**14.1. UN number:** UN 1206  
**14.2. UN proper shipping name:** HEPTANES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Marine pollutant: P  
Special Provisions: -  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-D

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1206  
**14.2. UN proper shipping name:** HEPTANES  
**14.3. Transport hazard class(es):** 3

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## BCY01

Revision date: 16.03.2021

Page 10 of 11

### 14.4. Packing group:

II

Hazard label:

3



Special Provisions:

A3

Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:

353

IATA-max. quantity - Passenger:

5 L

IATA-packing instructions - Cargo:

364

IATA-max. quantity - Cargo:

60 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes



Danger releasing substance:

Heptane

### 14.6. Special precautions for user

Warning: Combustible liquid.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 29, Entry 57

2010/75/EU (VOC):

100 % (700 g/l)

2004/42/EC (VOC):

100 % (700 g/l)

Information according to 2012/18/EU (SEVESO III):

E1 Hazardous to the Aquatic Environment

Additional information:

P5c

#### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,3.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



**BCY01**

Revision date: 16.03.2021

Page 11 of 11

IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Muta. 1B; H340	Calculation method
Carc. 1B; H350	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Activator	-	-	-	-	-	-	-	Aktivator

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*