

EP150

Revision date: 17.03.2021

Page 1 of 10

1. Identification**Product identifier**

EP150

UFI: 4600-604T-D00Y-5HS8

Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants

Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kjaer
Street: Im Tiefen See 45
Place: D-64293 Darmstadt
Telephone: +49 (0)6151 803-0
Internet: www.hbm.com
Responsible Department: support@hbm.com

Emergency telephone number: +49-30-18412-0**2. Hazard identification****Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Flammable liquid: Flam. Liq. 2
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Respiratory or skin sensitization: Skin Sens. 1
Specific target organ toxicity - single exposure: STOT SE 3 (narcotic effects)
Hazardous to the aquatic environment: Aquatic Chronic 3

Label elements**Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

Highly flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wear protective gloves/protective clothing/eye protection/face protection.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml**Signal word:** Danger

EP150

Revision date: 17.03.2021

Page 2 of 10

Pictograms:**Hazard statements**

H317-H412

Precautionary statements

P261-P280

Other hazards

No information available.

3. Composition/information on ingredients**Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
78-93-3	butanone; ethyl methyl ketone	35 - < 40 %
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	20 - < 25 %
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	15 - < 20 %
1330-20-7	xylene	10 - < 15 %
80-08-0	dapsone; 4,4'-diamino diphenyl sulfone	5 - < 10 %

Full text of H statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	20 - < 25 %
		Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
123-42-2	204-626-7	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	15 - < 20 %
		dermal: LD50 = 13630 mg/kg; oral: LD50 = 2520 mg/kg Eye Irrit. 2; H319: >= 10 - 100	
1330-20-7	215-535-7	xylene	10 - < 15 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
80-08-0	201-248-4	dapsone; 4,4'-diamino diphenyl sulfone	5 - < 10 %
		oral: ATE = 500 mg/kg	

Further Information

No information available.

4. First-aid measures**Description of first aid measures****General information**

Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

EP150

Revision date: 17.03.2021

Page 3 of 10

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water.

Most important symptoms and effects, whether acute or delayed

No information available.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

Specific hazards arising from the hazardous product

Highly flammable. Vapours can form explosive mixtures with air.

Special protective equipment and precautions for fire-fighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General measures**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

EP150

Revision date: 17.03.2021

Page 4 of 10

Vapours can form explosive mixtures with air.

Further information on handling

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent, strong , Combustible substances of acute toxicity, category 1 and 2 / very toxic substances Non-combustible substances of acute toxicity, category 1 and 2 / very toxic substances

Further information on storage conditions

Keep container tightly closed in a cool, well-ventilated place.

8. Exposure controls/Personal protection**Control parameters****Additional advice on limit values**

No information available.

Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

In use, may form flammable/explosive vapour-air mixture.

Use explosion-proof electrical equipment.

Use non-sparking tools.

Protective and hygiene measures

When using do not eat or drink.

Do not breathe gas/fumes/vapour/spray.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

Wear suitable protective clothing, gloves and eye/face protection.

Draw up and observe skin protection programme.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Thickness of the glove material: $\geq 0,7$ mm

Suitable gloves type NBR (Nitrile rubber)

Breakthrough time: ≥ 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Used working clothes should not be worn outside the work area.

Separate storage of work clothes.

EP150

Revision date: 17.03.2021

Page 5 of 10

Wear anti-static footwear and clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device (full mask or mouthpiece) with filter: a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	transparent	
Odour:	Adhesives, sealants	
pH-Value:		not determined

Changes in the physical state

Melting point:		not determined
Boiling point or initial boiling point and boiling range:		80 °C
Sublimation point:		not determined
Softening point:		not determined
Pour point:		not determined
not determined:		
Flash point:		-4 °C
Sustaining combustion:		No data available

Flammability

Solid/liquid:		not applicable
Gas:		not applicable

Explosive properties

No information available.

Lower explosive limits:		0,7 vol. %
Upper explosive limits:		11,5 vol. %
Auto-ignition temperature:		465 °C

Self-ignition temperature

Solid:		not applicable
Gas:		not applicable

Decomposition temperature:		not determined
----------------------------	--	----------------

Oxidizing properties

Not oxidising.

Vapour pressure:		8 hPa
(at 20 °C)		
Vapour pressure:		9 hPa
(at 50 °C)		
Density (at 20 °C):		0,934 g/cm ³
Bulk density:		not determined

EP150

Revision date: 17.03.2021

Page 6 of 10

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Viscosity / dynamic:

not determined

Viscosity / kinematic:

not determined

Flow time:

not determined

Relative vapour density:

not determined

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

69,50 %

Other information

Solid content:

not determined

10. Stability and reactivity**Reactivity**

Highly flammable.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

Incompatible materials

No information available.

Hazardous decomposition products

No known hazardous decomposition products.

Further information

No information available.

11. Toxicological information**Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

EP150

Revision date: 17.03.2021

Page 7 of 10

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol				
	oral	LD50 mg/kg	2520	Rat	
	dermal	LD50 mg/kg	13630	Rabbit	
1330-20-7	xylene				
	dermal	ATE mg/kg	1100		
	inhalation vapour	ATE	11 mg/l		
	inhalation aerosol	ATE	1,5 mg/l		
80-08-0	dapson; 4,4'-diamino diphenyl sulfone				
	oral	ATE mg/kg	500		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitizing effects

May cause an allergic skin reaction. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Practical experience

No information available.

Information on other hazards**Other information**

No information available.

Further information

No information available.

12. Ecological information**Ecotoxicity**

@1501.B015605

Persistence and degradability

The product has not been tested.

Bioaccumulative potential

The product has not been tested.

EP150

Revision date: 17.03.2021

Page 8 of 10

Mobility in soil

The product has not been tested.

Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

13. Disposal considerations**Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

14. Transport information**Canadian TDG**

<u>UN/ID number:</u>	UN 1133
<u>Proper shipping name:</u>	Adhesives
<u>Hazard classes:</u>	3
<u>Packing group:</u>	III
Hazard label:	3
Limited quantity:	5L

**Marine transport (IMDG)**

<u>UN number:</u>	UN 1133
<u>United Nations proper shipping name:</u>	Adhesives
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	III
Hazard label:	3



Special Provisions:	223, 955
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

<u>UN number:</u>	UN 1133
<u>United Nations proper shipping name:</u>	Adhesives
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	III

EP150

Revision date: 17.03.2021

Page 9 of 10

Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1

IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

15. Regulatory information**Canadian regulations****16. Other information****Changes**

This data sheet contains changes from the previous version in section(s): 3,8.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GHS

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H statements (number and full text)

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.

Safety Data Sheet



EP150

Revision date: 17.03.2021

Page 10 of 10

H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)