

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



EP150

Revision date: 17.03.2021

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

EP150

UFI: 4600-604T-D00Y-5HS8

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives, sealants

### 1.3. Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kjaer  
Street: Im Tiefen See 45  
Place: D-64293 Darmstadt  
Telephone: +49 (0)6151 803-0  
Internet: www.hbm.com  
Responsible Department: support@hbm.com

**1.4. Emergency telephone number:** +49-30-18412-0

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

butanone; ethyl methyl ketone

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)

**Signal word:** Danger

**Pictograms:**



#### Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 2 of 12

H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

### Special labelling of certain mixtures

Restricted to professional users.

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



### Hazard statements

H317-H412

### Precautionary statements

P261-P280

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
78-93-3	butanone; ethyl methyl ketone			35 - < 40 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)			20 - < 25 %
	500-033-5	603-074-00-8		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol			15 - < 20 %
	204-626-7	603-016-00-1		
	Eye Irrit. 2; H319			
1330-20-7	xylene			10 - < 15 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
80-08-0	dapson; 4,4'-diamino diphenyl sulfone			5 - < 10 %
	201-248-4	612-084-00-1		
	Acute Tox. 4; H302			

Full text of H and EUH statements: see section 16.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 3 of 12

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	20 - < 25 %
		Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
123-42-2	204-626-7	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	15 - < 20 %
		dermal: LD50 = 13630 mg/kg; oral: LD50 = 2520 mg/kg Eye Irrit. 2; H319: >= 10 - 100	
1330-20-7	215-535-7	xylene	10 - < 15 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
80-08-0	201-248-4	dapsone; 4,4'-diamino diphenyl sulfone	5 - < 10 %
		oral: ATE = 500 mg/kg	

### Further Information

No information available.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. First aider: Pay attention to self-protection!

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Rinse mouth immediately and drink plenty of water.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

#### Unsuitable extinguishing media

Water.

### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



EP150

Revision date: 17.03.2021

Page 4 of 12

surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General measures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### Further information on handling

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Do not store together with: Oxidising agent, strong , Combustible substances of acute toxicity, category 1 and 2 / very toxic substances Non-combustible substances of acute toxicity, category 1 and 2 / very toxic substances

#### Further information on storage conditions

Keep container tightly closed in a cool, well-ventilated place.

### 7.3. Specific end use(s)

Adhesives, sealants Adhesives, sealants

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 5 of 12

### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
123-42-2	Diacetone alcohol	50	240		TWA (8 h)	
78-93-3	Methyl ethyl ketone (MEK) (Butan-2-one)	200	600		TWA (8 h)	
		300	900		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

### Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	Butan-2-one	70 µmol/L	Urine	Post shift

### Additional advice on limit values

No information available.

### 8.2. Exposure controls



#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

In use, may form flammable/explosive vapour-air mixture.

Use explosion-proof electrical equipment.

Use non-sparking tools.

#### Protective and hygiene measures

When using do not eat or drink.

Do not breathe gas/fumes/vapour/spray.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

Wear suitable protective clothing, gloves and eye/face protection.

Draw up and observe skin protection programme.

#### Eye/face protection

Wear eye/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Thickness of the glove material:  $\geq 0,7$  mm

Suitable gloves type NBR (Nitrile rubber)

Breakthrough time:  $>480$  min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Used working clothes should not be worn outside the work area.

Separate storage of work clothes.

Wear anti-static footwear and clothing

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



EP150

Revision date: 17.03.2021

Page 6 of 12

## Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device (full mask or mouthpiece) with filter: a  
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

## Environmental exposure controls

Do not allow to enter into surface water or drains.  
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	transparent	
Odour:	Adhesives, sealants	
pH-Value:		not determined

#### Changes in the physical state

Melting point:		not determined
Boiling point or initial boiling point and boiling range:		80 °C
Sublimation point:		not determined
Softening point:		not determined
Pour point:		not determined
not determined:		
Flash point:		-4 °C
Sustaining combustion:		No data available

#### Flammability

Solid/liquid:		not applicable
Gas:		not applicable

#### Explosive properties

No information available.

Lower explosion limits:		0,7 vol. %
Upper explosion limits:		11,5 vol. %
Auto-ignition temperature:		465 °C

#### Self-ignition temperature

Solid:		not applicable
Gas:		not applicable

Decomposition temperature:		not determined
----------------------------	--	----------------

#### Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)		8 hPa
Vapour pressure: (at 50 °C)		9 hPa
Density (at 20 °C):		0,934 g/cm <sup>3</sup>
Bulk density:		not determined

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 7 of 12

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

### **Solubility in other solvents**

not determined

Partition coefficient n-octanol/water:

not determined

Viscosity / dynamic:

not determined

Viscosity / kinematic:

not determined

Flow time:

not determined

Relative vapour density:

not determined

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

69,50 %

### **9.2. Other information**

Solid content:

not determined

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

Highly flammable.

### **10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

### **10.3. Possibility of hazardous reactions**

No known hazardous reactions.

### **10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

### **10.5. Incompatible materials**

No information available.

### **10.6. Hazardous decomposition products**

No known hazardous decomposition products.

### **Further information**

No information available.

## **SECTION 11: Toxicological information**

### **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 8 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol				
	oral	LD50 mg/kg	2520	Rat	
	dermal	LD50 mg/kg	13630	Rabbit	
1330-20-7	xylene				
	dermal	ATE mg/kg	1100		
	inhalation vapour	ATE	11 mg/l		
	inhalation aerosol	ATE	1,5 mg/l		
80-08-0	dapson; 4,4'-diamino diphenyl sulfone				
	oral	ATE mg/kg	500		

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

### Sensitising effects

May cause an allergic skin reaction. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700))

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Specific effects in experiment on an animal

No information available.

### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### Practical experience

No information available.

## 11.2. Information on other hazards

### Other information

No information available.

### Further information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

@1501.B015605



# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 9 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol					
	Acute fish toxicity	LC50	420 mg/l	96 h	Lepomis macrochirus	

### 12.2. Persistence and degradability

The product has not been tested.

### 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	1,03

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

### 12.7. Other adverse effects

No information available.

### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Dispose of waste according to applicable legislation.

#### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Tunnel restriction code:	E

### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 10 of 12

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** III

Hazard label: 3



Classification code: F1

Limited quantity: 5 L

Excepted quantity: E1

### Marine transport (IMDG)

**14.1. UN number:** UN 1133

**14.2. UN proper shipping name:** Adhesives

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** III

Hazard label: 3



Special Provisions: 223, 955

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-D

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1133

**14.2. UN proper shipping name:** Adhesives

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** III

Hazard label: 3



Special Provisions: A3

Limited quantity Passenger: 10 L

Passenger LQ: Y344

Excepted quantity: E1

IATA-packing instructions - Passenger: 355

IATA-max. quantity - Passenger: 60 L

IATA-packing instructions - Cargo: 366

IATA-max. quantity - Cargo: 220 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

No information available.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 11 of 12

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): 32,5 % (303,55 g/l)

2004/42/EC (VOC): 69,5 % (649,13 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,8.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## EP150

Revision date: 17.03.2021

Page 12 of 12

H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*