

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

NG150

UFI: 1410-R0R5-S00E-E95Y

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Paints and varnishes

1.3. Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kjaer
Street: Im Tiefen See 45
Place: D-64293 Darmstadt
Telephone: +49 (0)6151 803-0
Internet: www.hbm.com
Responsible Department: support@hbm.com

1.4. Emergency telephone number: +49-30-18412-0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Germ cell mutagenicity: Muta. 2

Carcinogenicity: Carc. 1B

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

butanone; ethyl methyl ketone

phenol; carboic acid; monohydroxybenzene; phenylalcohol

formaldehyde ... %

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 2 of 11

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.

Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Special labelling of certain mixtures

EUH208	Contains formaldehyde ... %, di(benzothiazol-2-yl) disulphide. May produce an allergic reaction. Restricted to professional users.
--------	---

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H341-H350

Precautionary statements

P201-P280

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
78-93-3	butanone; ethyl methyl ketone			60 - < 70 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
108-95-2	phenol; carbolic acid; monohydroxybenzene; phenylalcohol			1 - < 2 %
	203-632-7	604-001-00-2		
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, STOT RE 2; H341 H331 H311 H301 H314 H373			
50-00-0	formaldehyde ... %			< 1 %
	200-001-8	605-001-00-5		
	Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1; H350 H341 H331 H311 H301 H314 H317			
120-78-5	di(benzothiazol-2-yl) disulphide			< 1 %
	204-424-9	613-135-00-0		
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410 EUH031			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-95-2	203-632-7	phenol; carboic acid; monohydroxybenzene; phenylalcohol	1 - < 2 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3	
50-00-0	200-001-8	formaldehyde ... %	< 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 5 - < 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 3; H335: >= 5 - 100	

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. First aider: Pay attention to self-protection!

After inhalation

When in doubt or if symptoms are observed, get medical advice.

Provide fresh air.

In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Dry extinguishing powder, Foam

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable.

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 4 of 11

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Do not allow to enter into surface water or drains. Treat the recovered material as prescribed in the section on waste disposal. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

Other information

Take up mechanically, placing in appropriate containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Further information on handling

Wear personal protection equipment (refer to section 8). Do not empty into drains. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.
Do not allow to enter into surface water or drains.
Do not allow uncontrolled discharge of product into the environment.

Hints on joint storage

TRGS 510

Further information on storage conditions

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 5 of 11

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
50-00-0	Formaldehyde	0.2	-		TWA (8 h)	
		0.4	-		STEL (15 min)	
78-93-3	Methyl ethyl ketone (MEK) (Butan-2-one)	200	600		TWA (8 h)	
		300	900		STEL (15 min)	
108-95-2	Phenol	2	8		TWA (8 h)	
		4	16		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	Butan-2-one	70 µmol/L	Urine	Post shift
108-95-2	Phenol	Phenol	120 mg/g	Creatinine	End of shift

Additional advice on limit values

No information available.

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
In use, may form flammable/explosive vapour-air mixture.
Use explosion-proof electrical equipment.
Use non-sparking tools.

Protective and hygiene measures

When using do not eat or drink.
Do not breathe gas/fumes/vapour/spray.
After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
Wear suitable protective clothing, gloves and eye/face protection.
Draw up and observe skin protection programme.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. EN ISO 374
The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Thickness of the glove material: $\geq 0,7\text{mm}$
Suitable gloves type NBR (Nitrile rubber)
Breakthrough time: $>480\text{ min}$

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 6 of 11

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Used working clothes should not be worn outside the work area.

Separate storage of work clothes.

Wear anti-static footwear and clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device (full mask or mouthpiece) with filter: a

Environmental exposure controls

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	yellow
Odour:	Ketone
pH-Value:	not determined

Changes in the physical state

Melting point:	not determined
Boiling point or initial boiling point and boiling range:	80 °C
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
not determined:	
Flash point:	9,7 °C
Sustaining combustion:	No data available

Flammability

Solid/liquid:	not determined
Gas:	not determined

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	1,5 vol. %
Upper explosion limits:	11,5 vol. %
Auto-ignition temperature:	475 °C

Self-ignition temperature

Solid:	not determined
Gas:	not determined
Decomposition temperature:	not determined

Oxidizing properties

not determined

Vapour pressure: (at 20 °C)	101 hPa
Vapour pressure: (at 50 °C)	not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 7 of 11

Density (at 20 °C):	0,9 g/cm ³
Bulk density:	not determined
Water solubility:	not determined
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Flow time:	not determined
Relative vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined

9.2. Other information

Solid content:	2,61 %
----------------	--------

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

Further information

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 8 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-95-2	phenol; carboic acid; monohydroxybenzene; phenylalcohol				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation aerosol	ATE 0,5 mg/l			
50-00-0	formaldehyde ... %				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation aerosol	ATE 0,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains formaldehyde ... %, di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (phenol; carboic acid; monohydroxybenzene; phenylalcohol; formaldehyde ... %)

May cause cancer. (formaldehyde ... %)

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Other information

No information available.

Further information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 9 of 11

CAS No	Chemical name	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-95-2	phenol; carboic acid; monohydroxybenzene; phenylalcohol						
	Acute algae toxicity	ErC50	229 mg/l	72 h		GESTIS	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-95-2	phenol; carboic acid; monohydroxybenzene; phenylalcohol	1,5

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1193
14.2. UN proper shipping name:	ETHYL METHYL KETONE (METHYL ETHYLKETONE)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number:	UN 1193
14.2. UN proper shipping name:	ETHYL METHYL KETONE (METHYL ETHYLKETONE)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 10 of 11



Classification code: F1
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1193
14.2. UN proper shipping name: ETHYL METHYL KETONE (METHYL ETHYLKETONE)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1193
14.2. UN proper shipping name: ETHYL METHYL KETONE (METHYL ETHYLKETONE)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 72

2010/75/EU (VOC): 2,49 % (22,41 g/l)

Safety Data Sheet

according to Regulation (EC) No 1907/2006



NG150

Revision date: 18.03.2021

Page 11 of 11

2004/42/EC (VOC): 77,68 % (699,12 g/l)
Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,8,15.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Muta. 2; H341	Calculation method
Carc. 1B; H350	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH031 Contact with acids liberates toxic gas.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains formaldehyde ... %, di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)