

SL450

Revision date: 14.09.2022

Page 1 of 10

## 1. Identification

### Product identifier

SL450

### Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Paints and varnishes

### Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kjaer  
Street: Im Tiefen See 45  
Place: D-64293 Darmstadt  
Telephone: +49 (0)6151 803-0  
Internet: www.hbm.com  
Responsible Department: support@hbm.com

**Emergency telephone number:** +49-30-18412-0

## 2. Hazard identification

### Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Acute Tox. 4; H332  
Skin Irrit. 2; H315  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### Label elements

#### Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



#### Hazard statements

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P233 Keep container tightly closed.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.

#### Special labelling of certain mixtures

Restricted to professional users.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

SL450

Revision date: 14.09.2022

Page 2 of 10

**Pictograms:****Hazard statements**

H412

**Other hazards**

No information available.

**3. Composition/information on ingredients****Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
1330-20-7	xylene	50 - < 55 %
100-41-4	ethylbenzene	10 - < 15 %
14324-55-1	zinc bis(diethyldithiocarbamate)	< 1 %
108-88-3	toluene	< 1 %

Full text of H statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	50 - < 55 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
100-41-4	202-849-4	ethylbenzene	10 - < 15 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
14324-55-1	238-270-9	zinc bis(diethyldithiocarbamate)	< 1 %
		oral: ATE = 500 mg/kg	
108-88-3	203-625-9	toluene	< 1 %
		inhalation: LC50 = 49 mg/l (vapours); dermal: LD50 = 12200 mg/kg	

**Further Information**

No information available.

**4. First-aid measures****Description of first aid measures****General information**

Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. First aider: Pay attention to self-protection!

**After inhalation**

When in doubt or if symptoms are observed, get medical advice.

Provide fresh air.

In case of respiratory tract irritation, consult a physician.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

SL450

Revision date: 14.09.2022

Page 3 of 10

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting.

**Most important symptoms and effects, whether acute or delayed**

No information available.

**Indication of immediate medical attention and special treatment needed**

No information available.

**5. Fire-fighting measures****Extinguishing media****Suitable extinguishing media**

Water spray jet, Dry extinguishing powder, Foam

**Unsuitable extinguishing media**

Full water jet

**Specific hazards arising from the hazardous product**

Highly flammable.

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Special protective equipment and precautions for fire-fighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

Co-ordinate fire-fighting measures to the fire surroundings.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Use personal protection equipment.

Do not allow to enter into surface water or drains. Treat the recovered material as prescribed in the section on waste disposal. Provide adequate ventilation.

**Environmental precautions**

Do not allow to enter into surface water or drains.

Do not allow uncontrolled discharge of product into the environment.

**Methods and material for containment and cleaning up****Other information**

Take up mechanically, placing in appropriate containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**7. Handling and storage**

SL450

Revision date: 14.09.2022

Page 4 of 10

**Precautions for safe handling****Advice on safe handling**

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on protection against fire and explosion**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**Further information on handling**

Wear personal protection equipment (refer to section 8). Do not empty into drains. When using do not eat, drink, smoke, sniff.

**Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed and in a well-ventilated place.

Do not allow to enter into surface water or drains.

Do not allow uncontrolled discharge of product into the environment.

**Hints on joint storage**

Do not store together with: Oxidising agent, strong , Combustible substances of acute toxicity, category 1 and 2 / very toxic substances Non-combustible substances of acute toxicity, category 1 and 2 / very toxic substances

**Further information on storage conditions**

Keep container tightly closed in a cool, well-ventilated place.

**8. Exposure controls/Personal protection****Control parameters****Additional advice on limit values**

No information available.

**Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

In use, may form flammable/explosive vapour-air mixture.

Use explosion-proof electrical equipment.

Use non-sparking tools.

**Protective and hygiene measures**

When using do not eat or drink.

Do not breathe gas/fumes/vapour/spray.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

Wear suitable protective clothing, gloves and eye/face protection.

Draw up and observe skin protection programme.

**Eye/face protection**

Wear eye/face protection.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working

## SL450

Revision date: 14.09.2022

Page 5 of 10

place concentration and quantity of hazardous substances.

Thickness of the glove material:  $\geq 0,7\text{mm}$

Suitable gloves type NBR (Nitrile rubber)

Breakthrough time:  $>480\text{ min}$

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Used working clothes should not be worn outside the work area.

Separate storage of work clothes.

Wear anti-static footwear and clothing

**Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device (full mask or mouthpiece) with filter: a

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

**9. Physical and chemical properties****Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	Solvents	
pH-Value:		not determined

**Changes in the physical state**

Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		136 °C
Sublimation point:		not determined
Softening point:		not determined
Pour point:		not determined
not determined:		

Flash point:		15 °C
Sustaining combustion:		No data available

**Flammability**

Solid/liquid:		not determined
Gas:		not determined

**Explosive properties**

not explosive according to EU A.14

Lower explosive limits:		0,7 vol. %
Upper explosive limits:		8,1 vol. %
Auto-ignition temperature:		430 °C

**Self-ignition temperature**

Solid:		not determined
Gas:		not determined
Decomposition temperature:		not determined

**Oxidizing properties**

No information available.

## SL450

Revision date: 14.09.2022

Page 6 of 10

Vapour pressure: (at 20 °C)	10 hPa
Vapour pressure: (at 50 °C)	47 hPa
Density (at 20 °C):	1,01 g/cm <sup>3</sup>
Bulk density:	not determined
Water solubility:	not determined
<b>Solubility in other solvents</b> not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Flow time:	not determined
Relative vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	70,25 %

**Other information**

Solid content:	0,99 %
No information available.	

**10. Stability and reactivity****Reactivity**

No information available.

**Chemical stability**

The substance is chemically stable under recommended conditions of storage, use and temperature.

**Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

**Conditions to avoid**

No information available.

**Incompatible materials**

No information available.

**Hazardous decomposition products**

No information available.

**Further information**

No information available.

**11. Toxicological information****Information on toxicological effects****Acute toxicity**

Harmful if inhaled.

**ATEmix calculated**

ATE (dermal) 2820,5 mg/kg; ATE (inhalation vapour) 23,57 mg/l; ATE (inhalation dust/mist) 2,941 mg/l

## SL450

Revision date: 14.09.2022

Page 7 of 10

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
14324-55-1	zinc bis(diethyldithiocarbamate)				
	oral	ATE 500 mg/kg			
108-88-3	toluene				
	dermal	LD50 12200 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 49 mg/l	Rat	GESTIS	

**Irritation and corrosivity**

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitizing effects**

Contains zinc bis(diethyldithiocarbamate). May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (ethylbenzene)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**Information on other hazards****Other information**

No information available.

**Further information**

No information available.

**12. Ecological information****Persistence and degradability**

## SL450

Revision date: 14.09.2022

Page 8 of 10

No information available.

**Bioaccumulative potential**

No information available.

**Mobility in soil**

No information available.

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other adverse effects**

No information available.

**13. Disposal considerations****Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

**14. Transport information****Canadian TDG**

<b><u>UN number or ID number:</u></b>	UN 1993
<b><u>Proper shipping name:</u></b>	Flammable liquid, n.o.s.
<b><u>Hazard classes:</u></b>	3
<b><u>Packing group:</u></b>	III
Hazard label:	3
Limited quantity:	5 L

**Marine transport (IMDG)**

<b><u>UN number:</u></b>	UN 1993
<b><u>United Nations proper shipping name:</u></b>	FLAMMABLE LIQUID, N.O.S. (Ethylbenzene, Xylene)
<b><u>Transport hazard class(es):</u></b>	3
<b><u>Packing group:</u></b>	III
Hazard label:	3



Special Provisions:	223, 274, 955
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

<b><u>UN number:</u></b>	UN 1993
<b><u>United Nations proper shipping name:</u></b>	FLAMMABLE LIQUID, N.O.S. (Ethylbenzene, Xylene)
<b><u>Transport hazard class(es):</u></b>	3



SL450

Revision date: 14.09.2022

Page 9 of 10

**Packing group:**

III

Hazard label:

3



Special Provisions:

A3

Limited quantity Passenger:

10 L

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

**Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:

No

**15. Regulatory information****Canadian regulations****16. Other information****Changes**

This data sheet contains changes from the previous version in section(s): 11.

**Classification for mixtures and used evaluation method according to GHS**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains zinc bis(diethylthiocarbamate). May produce an allergic reaction.

# Safety Data Sheet



**SL450**

Revision date: 14.09.2022

Page 10 of 10

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*