Print date: 17.03.2021

according to Regulation (EC) No 1907/2006

#### X120-B

Revision date: 17.03.2021 Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

X120-B

UFI: WQY5-Y7KH-C7FX-J0JG

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives, sealants

### 1.3. Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kiaer Street: Im Tiefen See 45 Place: D-64293 Darmstadt +49 (0)6151 803-0 Telephone: Internet: www.hbm.com Responsible Department: support@hbm.com 1.4. Emergency telephone +49-30-18412-0

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Carcinogenicity: Carc. 2

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer.

Toxic to aquatic life with long lasting effects.

# 2.2. Label elements

# Regulation (EC) No. 1272/2008

# Hazard components for labelling

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 1,4-Bis[(2,3-epoxypropoxy)methyl] cyclohexan

titanium dioxide

Signal word: Warning

Pictograms:







### **Hazard statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H351 Suspected of causing cancer.



Print date: 17.03.2021

according to Regulation (EC) No 1907/2006

X120-B

Revision date: 17.03.2021 Page 2 of 10

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P333 If skin irritation or rash occurs: P313 Get medical advice/attention.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P273 Avoid release to the environment.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:







**Hazard statements** 

H317-H351

**Precautionary statements** 

P313-P280

2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures



according to Regulation (EC) No 1907/2006

### X120-B

Revision date: 17.03.2021 Page 3 of 10

#### **Hazardous components**

CAS No	Chemical name					
	EC No	Index No	REACH No			
	GHS Classification					
25068-38-6	reaction product: bisphenol-A-(ep 700)	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)				
	500-033-5	603-074-00-8				
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens	s. 1, Aquatic Chronic 2; H315 H319 H3	317 H411			
14228-73-0	1,4-Bis[(2,3-epoxypropoxy)methy	l] cyclohexan		10 - 20 %		
	238-098-4					
	Skin Sens. 1; H317					
13463-67-7	titanium dioxide					
	236-675-5	022-006-00-2				
	Carc. 2; H351					
67762-90-7	Dimethylsiloxan, reaktionsprodukt mit Siliciumdioxid					
	614-122-2					
2530-83-8	[3-(2,3-Epoxypropoxy)propyl]trimo	ethoxysilaan		1 - < 5 %		
	219-784-2					
	Eye Dam. 1; H318					
2602-34-8	3-(2,3-Epoxypropyloxy)propyltriethoxysilane					
	220-011-6					

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

opositio solito: militatio di militati			
CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	40 - 70 %
	Skin Irrit. 2; H315: >= 5 - 100		

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. First aider: Pay attention to self-protection!

### After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

# After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

# After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.



according to Regulation (EC) No 1907/2006

#### X120-B

Revision date: 17.03.2021 Page 4 of 10

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray jet, Dry extinguishing powder, Foam

### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Co-ordinate fire-fighting measures to the fire surroundings.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### **General measures**

Do not breathe gas/vapour/aerosol. Provide adequate ventilation as well as local exhaustion at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Use personal protection equipment. Personal protection equipment: see section 8

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow uncontrolled discharge of product into the environment.

# 6.3. Methods and material for containment and cleaning up

#### Other information

Take up mechanically, placing in appropriate containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

### Advice on protection against fire and explosion

No special technical protective measures are necessary.

#### Further information on handling

Wear personal protection equipment (refer to section 8). Do not empty into drains. When using do not eat, drink, smoke, sniff.



according to Regulation (EC) No 1907/2006

#### X120-B

Revision date: 17.03.2021 Page 5 of 10

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

### Further information on storage conditions

No information available.

### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
1333-86-4	Carbon black (Inhalable Fraction)	-	3		TWA (8 h)	
13463-67-7	Titanium dioxide, total inhalable dust	-	10		TWA (8 h)	

#### 8.2. Exposure controls









### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

# Protective and hygiene measures

When using do not eat or drink. Do not breathe gas/fumes/vapour/spray.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Wear suitable protective clothing, gloves and eye/face protection.

Draw up and observe skin protection programme.

### Eye/face protection

Wear eye/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Thickness of the glove material: >= 0,7mm

Suitable gloves type NBR (Nitrile rubber)

Breakthrough time::>480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Used working clothes should not be worn outside the work area. Separate storage of work clothes.

#### Respiratory protection

not relevant

### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

L HBM

according to Regulation (EC) No 1907/2006

### X120-B

Revision date: 17.03.2021 Page 6 of 10

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: solid Colour: black

Odour: Epoxy resin dispersions

pH-Value: not relevant

Changes in the physical state

Melting point: not determined

Boiling point or initial boiling point and not determined

boiling range:

Sublimation point: not determined
Softening point: not determined
Pour point: not determined

not determined:

Flash point: 113 °C Sustaining combustion: No data available

**Flammability** 

Solid/liquid: not determined
Gas: not determined

**Explosive properties** 

not determined

Lower explosion limits:

Upper explosion limits:

not determined

not determined

Auto-ignition temperature:

not determined

Self-ignition temperature

Solid: not determined
Gas: not determined

Decomposition temperature: not determined

**Oxidizing properties** 

not determined

Vapour pressure: 15,2 hPa

(at 20 °C)

Vapour pressure: not determined

(at 50 °C)

Density (at 20 °C):

Bulk density:

not determined

not determined

water solubility:

not determined

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Viscosity / dynamic:

Not determined

Viscosity / kinematic:

Not determined

Flow time:

Relative vapour density:

Evaporation rate:

not determined

not determined

not determined



according to Regulation (EC) No 1907/2006

X120-B

Revision date: 17.03.2021 Page 7 of 10

Solvent separation test: not determined Solvent content: not determined

9.2. Other information

Solid content: 5,00 %

No information available.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

## 10.4. Conditions to avoid

No information available.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No information available.

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

# Sensitising effects

May cause an allergic skin reaction. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700); 1,4-Bis[(2,3-epoxypropoxy)methyl] cyclohexan)

## Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (titanium dioxide)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

### 12.1. Toxicity



according to Regulation (EC) No 1907/2006

### X120-B

Revision date: 17.03.2021 Page 8 of 10

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
2530-83-8	[3-(2,3-Epoxypropoxy)propyl]trimethoxysilaan						
	Acute fish toxicity	LC50	55 mg/l		Cyprinus carpio (Common Carp)	US-EPA	
	Acute crustacea toxicity	EC50	324 mg/l		Daphnia magna (Big water flea)	US-EPA	

### 12.2. Persistence and degradability

No information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation		-	
2530-83-8	[3-(2,3-Epoxypropoxy)propyl]trimethoxysilaan			
	BSB5	37%	28	ECHA
	BSB	370 mg/g	28	

## 12.3. Bioaccumulative potential

No information available.

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

No information available.

# 12.7. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

# **Disposal recommendations**

Dispose of waste according to applicable legislation.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

**14.1. UN number:** UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (festes

Epoxidharz)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Classification code:

IVI /

Special Provisions: 274 335 375 601

Limited quantity: 5 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -

НВМ

according to Regulation (EC) No 1907/2006

X120-B

Revision date: 17.03.2021 Page 9 of 10

Inland waterways transport (ADN)

**14.1. UN number:** UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (festes

Epoxidharz)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Classification code: M7

Special Provisions: 274 335 375 601

Limited quantity: 5 kg Excepted quantity: E1

Marine transport (IMDG)

**14.1. UN number:** UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(EPOXY RESIN)

14.3. Transport hazard class(es):
14.4. Packing group:

14.4. Packing group:IIIHazard label:9



9

Special Provisions: 274, 335, 966, 967, 969

Limited quantity: 5 kg
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: A97 A158 A179 A197

Limited quantity Passenger: 30 kg G
Passenger LQ: Y956
Excepted quantity: E1

IATA-packing instructions - Passenger: 956
IATA-max. quantity - Passenger: 400 kg
IATA-packing instructions - Cargo: 956
IATA-max. quantity - Cargo: 400 kg

14.5. Environmental hazards



according to Regulation (EC) No 1907/2006

X120-B

Revision date: 17.03.2021 Page 10 of 10

ENVIRONMENTALLY HAZARDOUS: Yes



# 14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

2010/75/EU (VOC): 15 %

Information according to 2012/18/EU E2 Hazardous to the Aquatic Environment

(SEVESO III):

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

## 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,8.

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 2; H351	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)