

NG150

Revision date: 26.05.2021

Page 1 of 9

## 1. Identification

### Product identifier

NG150

UFI: 1410-R0R5-S00E-E95Y

### Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Paints and varnishes

### Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kjaer  
Street: Im Tiefen See 45  
Place: D-64293 Darmstadt  
Telephone: +49 (0)6151 803-0  
Internet: www.hbm.com  
Responsible Department: support@hbm.com

**Emergency telephone number:** +49-30-18412-0

## 2. Hazard identification

### Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Flammable liquid: Flam. Liq. 2  
Skin corrosion/irritation: Skin Irrit. 2  
Serious eye damage/eye irritation: Eye Irrit. 2  
Germ cell mutagenicity: Muta. 2  
Carcinogenicity: Carc. 1B  
Specific target organ toxicity - single exposure: STOT SE 3 (narcotic effects)

### Label elements

#### Regulation (EC) No. 1272/2008

**Signal word:** Danger

**Pictograms:**



#### Hazard statements

Highly flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing genetic defects.  
May cause cancer.

#### Precautionary statements

Obtain special instructions before use.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear protective gloves/protective clothing/eye protection/face protection.

#### Special labelling of certain mixtures

Restricted to professional users.

#### Labelling of packages where the contents do not exceed 125 ml

**Signal word:** Danger

## NG150

Revision date: 26.05.2021

Page 2 of 9

## Pictograms:



## Hazard statements

H341-H350

## Precautionary statements

P201-P280

## Other hazards

No information available.

## 3. Composition/information on ingredients

## Mixtures

## Hazardous components

CAS No	Chemical name	Quantity
78-93-3	butanone; ethyl methyl ketone	60 - < 70 %
108-95-2	phenol; carbolic acid; monohydroxybenzene; phenylalcohol	1 - < 2 %
50-00-0	formaldehyde ... %	< 1 %
120-78-5	di(benzothiazol-2-yl) disulphide	0.1 - < 1% (*)

Full text of H statements: see section 16.

(\*) The actual concentration is withheld as a trade secret.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-95-2	203-632-7	phenol; carbolic acid; monohydroxybenzene; phenylalcohol	1 - < 2 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3	
50-00-0	200-001-8	formaldehyde ... %	< 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 5 - < 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 3; H335: >= 5 - 100	

## Further Information

No information available.

## 4. First-aid measures

## Description of first aid measures

## General information

Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. First aider: Pay attention to self-protection!

## After inhalation

When in doubt or if symptoms are observed, get medical advice.

Provide fresh air.

In case of respiratory tract irritation, consult a physician.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

## NG150

Revision date: 26.05.2021

Page 3 of 9

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting.

**Most important symptoms and effects, whether acute or delayed**

No information available.

**Indication of immediate medical attention and special treatment needed**

No information available.

**5. Fire-fighting measures****Extinguishing media****Suitable extinguishing media**

Water spray jet, Dry extinguishing powder, Foam

**Unsuitable extinguishing media**

Full water jet

**Specific hazards arising from the hazardous product**

Highly flammable.

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Special protective equipment and precautions for fire-fighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

Co-ordinate fire-fighting measures to the fire surroundings.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures****General measures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Do not allow to enter into surface water or drains. Treat the recovered material as prescribed in the section on waste disposal. Provide adequate ventilation.

**Environmental precautions**

Do not allow to enter into surface water or drains.

Do not allow uncontrolled discharge of product into the environment.

**Methods and material for containment and cleaning up****Other information**

Take up mechanically, placing in appropriate containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**7. Handling and storage**

**Precautions for safe handling****Advice on safe handling**

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on protection against fire and explosion**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**Further information on handling**

Wear personal protection equipment (refer to section 8). Do not empty into drains. When using do not eat, drink, smoke, sniff.

**Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed and in a well-ventilated place.

Do not allow to enter into surface water or drains.

Do not allow uncontrolled discharge of product into the environment.

**Hints on joint storage**

TRGS 510

**Further information on storage conditions**

Keep container tightly closed in a cool, well-ventilated place.

**8. Exposure controls/Personal protection****Control parameters****Additional advice on limit values**

No information available.

**Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

In use, may form flammable/explosive vapour-air mixture.

Use explosion-proof electrical equipment.

Use non-sparking tools.

**Protective and hygiene measures**

When using do not eat or drink.

Do not breathe gas/fumes/vapour/spray.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

Wear suitable protective clothing, gloves and eye/face protection.

Draw up and observe skin protection programme.

**Eye/face protection**

Wear eye/face protection.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

## NG150

Revision date: 26.05.2021

Page 5 of 9

Thickness of the glove material:  $\geq 0,7\text{mm}$

Suitable gloves type NBR (Nitrile rubber)

Breakthrough time:  $>480\text{ min}$

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Used working clothes should not be worn outside the work area.

Separate storage of work clothes.

Wear anti-static footwear and clothing

**Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device (full mask or mouthpiece) with filter: a

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

**9. Physical and chemical properties****Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	yellow	
Odour:	Ketone	
pH-Value:		not determined

**Changes in the physical state**

Melting point:		not determined
Boiling point or initial boiling point and boiling range:		80 °C
Sublimation point:		not determined
Softening point:		not determined
Pour point:		not determined
not determined:		
Flash point:		9,7 °C
Sustaining combustion:		No data available

**Flammability**

Solid/liquid:		not determined
Gas:		not determined

**Explosive properties**

In use, may form flammable/explosive vapour-air mixture.

Lower explosive limits:		1,5 vol. %
Upper explosive limits:		11,5 vol. %
Auto-ignition temperature:		475 °C

**Self-ignition temperature**

Solid:		not determined
Gas:		not determined
Decomposition temperature:		not determined

**Oxidizing properties**

not determined

## NG150

Revision date: 26.05.2021

Page 6 of 9

Vapour pressure: (at 20 °C)	101 hPa
Vapour pressure: (at 50 °C)	not determined
Density (at 20 °C):	0,9 g/cm <sup>3</sup>
Bulk density:	not determined
Water solubility:	not determined
<b>Solubility in other solvents</b> not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Flow time:	not determined
Relative vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined

**Other information**

Solid content: 2,61 %

**10. Stability and reactivity****Reactivity**

No information available.

**Chemical stability**

The substance is chemically stable under recommended conditions of storage, use and temperature.

**Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

**Conditions to avoid**

No information available.

**Incompatible materials**

No information available.

**Hazardous decomposition products**

No information available.

**Further information**

No information available.

**11. Toxicological information****Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

## NG150

Revision date: 26.05.2021

Page 7 of 9

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
108-95-2	phenol; carboic acid; monohydroxybenzene; phenylalcohol				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation aerosol	ATE 0,5 mg/l			
50-00-0	formaldehyde ... %				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation aerosol	ATE 0,5 mg/l			

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Sensitizing effects**

Contains formaldehyde ... %, di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of causing genetic defects. (phenol; carboic acid; monohydroxybenzene; phenylalcohol; formaldehyde ... %)

May cause cancer. (formaldehyde ... %)

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**Information on other hazards****Other information**

No information available.

**Further information**

No information available.

**12. Ecological information****Persistence and degradability**

No information available.

**Bioaccumulative potential**

## NG150

Revision date: 26.05.2021

Page 8 of 9

No information available.

**Mobility in soil**

No information available.

**Other adverse effects**

No information available.

**13. Disposal considerations****Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

**14. Transport information****Canadian TDG**

<b><u>UN/ID number:</u></b>	UN 1193
<b><u>Proper shipping name:</u></b>	Ethyl methyl ketone
<b><u>Hazard classes:</u></b>	3
<b><u>Packing group:</u></b>	II
Hazard label:	3
Limited quantity:	1L

**Marine transport (IMDG)**

<b><u>UN number:</u></b>	UN 1193
<b><u>United Nations proper shipping name:</u></b>	ETHYL METHYL KETONE (METHYL ETHYLKETONE)
<b><u>Transport hazard class(es):</u></b>	3
<b><u>Packing group:</u></b>	II
Hazard label:	3



Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-D
Segregation group:	1 - acids

**Air transport (ICAO-TI/IATA-DGR)**

<b><u>UN number:</u></b>	UN 1193
<b><u>United Nations proper shipping name:</u></b>	Ethyl metyl ketone
<b><u>Transport hazard class(es):</u></b>	3
<b><u>Packing group:</u></b>	II
Hazard label:	3



## NG150

Revision date: 26.05.2021

Page 9 of 9



Special Provisions:	A3	
Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

**Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**15. Regulatory information****Canadian regulations****16. Other information****Changes**

This data sheet contains changes from the previous version in section(s): 14.

**Classification for mixtures and used evaluation method according to GHS**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Muta. 2; H341	Calculation method
Carc. 1B; H350	Calculation method
STOT SE 3; H336	Calculation method

**Relevant H statements (number and full text)**

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH031	Contact with acids liberates toxic gas.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains formaldehyde ... %, di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*